

V-RECON SERIES VBIP-2IR-A

2 Megapixel Day/Night IR Bullet Camera



Key Features

- Day/Night Bullet with IR LED
- 2.8-12mm Varifocal Lens
- D-WDR
- IR Distance 40-50.
- Free Software for Mobile (Android / iPhone / iPad)
- Multi browser support for Safari, Chrome, IE, Firefox, and Opera

Recommended Accessories



- VPS-12810
- VPS-121630

Specifications	
Camera	
Sensor	Aptina AR0330 1/3" CMOS
Max. Resolution/FPS	1920(H) x 1080(V)30fps
Min. Illumination	Color: 0.2Lux@(F1.2, AGC ON, 50IRE, 3200K) B/W: 0Lux@(F1.2, AGC ON, 50IRE, 3200K, IR LED ON)
Day/Night	True Day / Night with ICR Filter
D-WDR	Yes, up to 78.4dB
IR Distance	40-50m
Lens	2.8-12mm
Electronic Shutter	Auto / User 1/5 - 1/2, 0000; 50/60Hz Software Selectable
Parameters	
Compression	H-264 High Profile (Support Baseline Profile) / MJPEG
Bit Rate	Stream1 500Kbps - 12Mbps ; Stream2 100Kbps - 6Mbps
Quality setting	1 - 9 (9 Highest)
Multi-Streaming	User setting of Stream 1/2 at supported Resolutions
Brightness/Sharpness	Variable 0~100 / 0~100
Gain Control	Auto / Manual
S/N	>50dB
Orientation	Horizontal Mirror / Vertical Flip
Text Overlay	Time / Date / Camera / Custom OSD
Motion Detection	Max 8 Areas
Masking	4 User defined masking areas < 8% of total picture>
Corridor Mode	On / Off
Reset	Yes
Network	
Ethernet	1 Ethernet (10/100 Base-T) RJ-45 Connector
Compliance	Onvif v2.2 Profile-S Listed
Web Language	English, Chinese
Network Protocols	IPV4,HTTPS, TCP/UDP, RTSP, FTP, DHCP, PPoE,DDNS,SMTP
Heart Beat	Yes
Max. User Access	6 (max 2 users for 1080P)
General	
Power Consumption	DC12V $\pm$ 10% ,POE 802.3af(POE optional) 2.5W Max(IR LED OFF) / 5W Max(IR LED ON) / 7W Max(HEATER ON)
Operating Humidity	0% - 95% RH
Approvals	CE / FCC / RoHS Compliant / IP66
Product Dimensions	101.3mm x 97.3mm x 298.2
Product Weight	Approximately 1.5lb (700g)